


Cellophane™ 220MT33 Nitrocellulose Coated Cellulose Film



Product Features

DESCRIPTION: A regenerated cellulose film, coated on both sides with nitrocellulose (N/C) by a solvent process. This material is NOT heat sealable.

FEATURES:

- Excellent Dead-Fold Characteristics
- Barrier to Water Vapor, Gasses and Aromas
- Anti-Static
- High Gloss and Transparency
- Resistant to Oils and Greases
- Receptive to Inks, Adhesives and Tear Tapes
- Biodegradable Base Film

APPLICATIONS:

- Twist and Bunch Wrapping of Hot and Sticky Candy Products (i.e. Caramel, Nougats on High Speed Machinery)

Property		Value	Unit	Test Method
Physical Properties				
Thickness		87	gauge	
Yield		22,000	in ² /lb	
Tensile Strength	MD	17,000	PSI	ASTM D 882
	TD	9,000		
Elongation	MD	22	%	ASTM D 882
	TD	70		
COF (film to film)	Static	0.25		ASTM D 1894
	Dynamic	0.20		
Elasticity Modulus	MD	>290,000	PSI	ASTM D 882
	TD	>145,000		
Optical Properties				
Haze		4	%	ASTM D 1003
Gloss		90	%	ASTM D 2457
Barrier Properties				
Water Vapor Transmission		1.3	g/100in ² /24hrs	100°F x 90% RH
Oxygen Transmission		0.19	cc/100in ² /24hrs	75°F x 0-5% RH

* All values +/- 10%

Food Contact: Cellophane™ MT is suitable for most applications involving direct contact with foodstuffs. Nitrocellulose coated films are manufactured to meet current food contact regulations relating to regenerated cellulose films, including FDA regulation 21 CFR 177.1200.

Film Storage: Cellophane™ MT should be stored in its original wrapping away from any source of local heating or direct sunlight at temperatures between 60-75°F and at a relative humidity of 35-55%. Cellophane™ MT is suitable for use for 6 months from the date of delivery, and stocks should be used in rotation.

Standard Roll Sizes

Available Core Sizes →	3"	3"	3"	6"
Approximate Roll OD →	9.5	13	18	18¾"
Standard Cellophane Gauges	Approximate Roll Lengths			
76	6,500	13,000	26,000	
86	5,700	11,400	22,800	
87	5,700	11,400	22,800	
90	5,700	11,400	22,800	
99	5,000	10,000	20,000	
100	5,000	10,000	20,000	
121	4,100	8,200	16,400	
137	3,600	7,200	14,400	
150	3,600	7,200	14,400	
160	3,000	6,000	12,000	
164	3,000	6,000	12,000	
170	2,900	5,750	11,500	

*Non-standard roll lengths/OD's are available on special request.

Available Widths


- Most films are available in roll widths from ¼ inch to 80 inches

Minimum Order Quantities

- Minimum order quantity is 500 lbs. Freight will be prepaid and added to invoice.
- Production orders less than 500 lbs. will incur a less than minimum order fee.
- Orders greater than 1000 lbs. are shipped freight paid.

Plant Locations

Nationwide service through four plants locations.



The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of Interfilm Holdings, Inc., and Interfilm Holdings, Inc., makes no warranty of results to be obtained. Users should make their own tests to determine the suitability of these products for their own particular purposes. However, because of the numerous factors affecting results, Interfilm Holdings, Inc., MAKES NO REPRESENTATIONS OF ANY WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY, FITNESS FOR PARTICULAR PURPOSE, OR ANY OTHER MATTER WITH RESPECT TO THE MATERIAL OTHER THAN THAT THE MATERIAL CONFORMS TO ITS APPLICABLE CURRENT STANDARD SPECIFICATIONS. Statements herein, therefore, should not be construed as representations or warranties. THE RESPONSIBILITY OF INTERFILM HOLDINGS, INC. FOR CLAIMS ARISING OUT OF BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY OR OTHERWISE IS LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.