

### Interfilm Type DWF Clear Transparent Window Film



## Product Features

**DESCRIPTION:** A low dusting, transparent, biaxially oriented polystyrene film designed for window envelope patches.

### FEATURES:

- Low Dust
- Transparent
- Good Dimensional Stability

### APPLICATIONS:

- Window Envelope Patches

Property		Value			Unit	Test Method
<b>Physical Properties</b>						
Thickness		115	125	150	gauge	
Yield		22,955	21,120	17,600	in <sup>2</sup> /lb	ASTM D 2103
Tensile Strength	MD	12,000			PSI	ASTM D 882
	TD	11,000				
Elongation	MD	20			%	ASTM D 882
	TD	40				
1% Secant Modulus	MD	435,000			PSI	ASTM D 882
	TD	430,000				
Tear Strength	TD	4			g/mil	ASTM D 882
<b>Optical Properties</b>						
Gloss		150			%	ASTM D 2457
Haze		8			%	ASTM D 1003

\* All values +/- 10%

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of Interfilm Holdings, Inc., and Interfilm Holdings, Inc., makes no warranty of results to be obtained. Users should make their own tests to determine the suitability of these products for their own particular purposes. However, because of the numerous factors affecting results, Interfilm Holdings, Inc., MAKES NO REPRESENTATIONS OF ANY WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY, FITNESS FOR PARTICULAR PURPOSE, OR ANY OTHER MATTER WITH RESPECT TO THE MATERIAL OTHER THAN THAT THE MATERIAL CONFORMS TO ITS APPLICABLE CURRENT STANDARD SPECIFICATIONS. Statements herein, therefore, should not be construed as representations or warranties. THE RESPONSIBILITY OF INTERFILM HOLDINGS, INC. FOR CLAIMS ARISING OUT OF BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY OR OTHERWISE IS LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.

## Standard Roll Sizes

Available Core Sizes →	3"	3"
Approximate Roll OD →	13	18
<b>Gauge</b>	<b>Approximate Roll Lengths</b>	
105	9,500	19,000
115	8,500	17,000
125	8,000	16,000
150	6,700	13,400

\*Non-standard roll lengths/OD's are available on special request.

---

## Available Widths

- Most films are available in roll widths from ¼ inch to 80 inches

---

## Minimum Order Quantities

- Minimum order quantity is 500 lbs. Freight will be prepaid and added to invoice.
- Production orders less than 500 lbs. will incur a less than minimum order fee.
- Orders greater than 1000 lbs. are shipped freight paid.

---

## Plant Locations

Nationwide service through four plants locations.

